

Compact Beam Shaper for a TopHat of 10.5 x 10.5 mm²

IOS000324



General Description:

| Advanced Optical Solutions |

This compact beam shaper is designed for a fiber coupled diode laser to generate a homogeneous field of 10.5 x 10.5 mm² in a working distance of approximately 300 mm.

Specification data of the laser source

	Unit	Value
Wavelength	nm	790 - 990
Power	W	≤ 120
Fiber core diameter	µm	400
NA		0.22
Fiber connector		SMA905

Specification data of the beam shaper module

	Unit	Value
Wavelength	nm	790 - 990
Generated field size ¹	mm ²	10.5 x 10.5 (top hat region)
Inhomogeneity ² (I _{max} -I _{min})/(I _{max} +I _{min})	%	≤ 7.5 (integrated over the other axis)
Working distance WD	mm	300 ± 10
Transmission	%	> 95
Length of the housing	mm	80.0 ± 0.1
Diameter of the housing	mm	30.5 ± 0.1

¹ The generated field size depends on the working distance. Not all combinations of field size and working distance are available.

² I_{max} and I_{min} denote the maximum and minimum intensity in the uniform field, respectively.

Options

Higher power

Different wavelength

High-spec version with reduced non-uniformity and steeper edges of the homogeneous field

Different generated field size and field geometry

RoHS compliant
2002/95/EG

Copyright © 2011 LIMO GmbH. All rights reserved. All LIMO products are patent pending.
Subject to change without notice.

Version May 20, 2019